



# WELD PACKAGE POWER CLUTCH

The **Weld Package** for your Welding Tasks  
from the Power Source to the Contact Tip

## AIR-COOLED



## CONTENT

Power Source • Weld Process  
Controller • Software •  
Interface • Wire Feeder Unit •  
Wire Guidance •  
Cable Bundle • Control Cable •  
Torch System • Torch Necks •  
Consumables

## WELDING PROCESSES

GMAW  
KF-pulse  
Pulse  
MIG-Brazing



**STEEL**

# SKS Weld Package: System design

## The Power Clutch Weld Package contains:

- A Integrated solution: power source, weld process controller and interface in one device
- 1 Power Source
- 2 Weld Process Controller and Software/IT
- 3 Robot Interface
- 4 Wire Feeder
- 5 Wire Guidance
- 6 Ground Cable
- 7 Control Cable
- 8 Cable Bundle
- 9 Torch System Power Clutch
- 10 Torch Neck/Consumables
- 11 Reamer Blades
- 12 TCP Dimensions/Checking Fixtures/Torch Cleaning Stations



## For installations with outer cable dress.


This brochure contains information about the SKS Weld Package, the torch system Power Clutch, as well as consumables and spare parts. There are various features of the welding machine components and torch systems available depending on the robot system and the welding task.

The **Power Clutch Weld Package** can be used with all common industrial robots.

A



Components 1, 2 & 3  
also available as an integrated  
solution – LSQ COMPACT.



## Power Clutch – air-cooled for steel applications

|                        |                                           |
|------------------------|-------------------------------------------|
| <b>Processes:</b>      | GMAW, KF-pulse, Pulse, MIG-Brazing        |
| <b>Wire materials:</b> | high-alloy steels, low-alloy steels       |
| <b>Compatibility:</b>  | for all common industrial robots          |
| <b>Weight:</b>         | 2.5 kg                                    |
| <b>Max. power:</b>     | 420 A – 60 % duty cycle/40 °C, air-cooled |
| <b>Wire diameter:</b>  | 0.8-1.6 mm                                |
| <b>TCP accuracy:</b>   | ± 0.2 ( 400 mm)                           |

## LSQ COMPACT



The LSQ COMPACT IoT was designed as an integrated welding system, combining the weld process controller, Fieldbus interface, and power supply into one unit, resulting in a compact size with fewer external connections – for easy installation. Even with its compact size and integrated design, this machine is powerful and incorporates 35 years of technological knowledge. Whether you are welding thick aluminum plates or thin stainless steel, a process is available to support your specific needs. All processes are unlocked and readily available. You do not need an additional license or passcode to use them.

**Up Front Pricing:**

**No hidden costs for  
welding processes  
and software functions.**

## A Integrated Solution LSQ COMPACT

Compact: All in One, All Inclusive. Compatible with  
SKS Weld Packages: Power Clutch, Power Joint and Frontpull.

**READY FOR  
GLOBAL USE**  
CE, UL & CCC  
CERTIFIED

**MQTT  
OPC UA\*\***  
+ TRACEABILITY



**POWER SOURCE**  
+ PROCESS CONTROLLER  
+ ROBOT INTERFACE

### **MATERIALS:**

steel  
low- & high-alloy steel  
copper alloys  
galvanized steel  
aluminum\*



**FREE WELD DATA  
DOCUMENTATION  
& MANAGEMENT**

**420 A**  
60% DUTY CYCLE  
**AT 40°C**

### **INCLUDES THE WELDING PROCESSES AND FUNCTIONS:**

GMAW  
I-pulse  
KF-pulse  
microMIG\*  
microMIG-cc\*  
MMT-x\*  
DP-Fast  
MIG-Brazing  
Synchroweld  
AutoComp

\* Only in combination with Frontpull torch system. Further information can be found in the Frontpull Weld Package

\*\* Only available in LSQ COMPACT IoT

# A Integrated Solution LSQ COMPACT



LSQ3 COMPACT Lite



LSQ5 COMPACT IoT

## Integrated power source

The LSQ COMPACT Lite and IoT are available with LSQ 3 and LSQ 5 power sources to provide the best solution for your application. The technical data can be found on the following pages.

## Integrated weld process controller

While the LSQ COMPACT Lite is designed for maximum cost efficiency, the LSQ COMPACT IoT offers additional features such as the Internet of Things (IoT), MQTT, and OPC UA support. This advanced weld process controller enables extended real-time monitoring and analysis of welding processes, resulting in improved quality assurance and more precise control of the process.

| Specifications | Lite              | IoT                    |
|----------------|-------------------|------------------------|
| Operation via  | buttons           | touch screen           |
| Programs       | 15.872            | 15.872                 |
| Ports          | USB, SD card slot | Ethernet, SD card slot |
| MQTT / OPC UA  | No                | Yes                    |
| Remote Control | Q8Tool            | Q8Tool, VNC client     |

## Integrated interface

With the included Fieldbus Interface FB5 the system can be perfectly integrated into existing Fieldbus environments. Various Fieldbus types are available e.g. EtherNet/IP, Profinet CU.

| Overview LSQ COMPACT  | Part-No.           |
|-----------------------|--------------------|
| LSQ5 COMPACT Lite     | <b>77-1185-71x</b> |
| LSQ3 COMPACT Lite     | <b>77-1184-78x</b> |
| LSQ5 COMPACT IoT      | <b>77-1185-77x</b> |
| LSQ3 COMPACT IoT      | <b>77-1184-81x</b> |
| LSQ5 CCC COMPACT Lite | <b>77-1185-73x</b> |
| LSQ3 CCC COMPACT Lite | <b>77-1184-73x</b> |
| LSQ5 CCC COMPACT IoT  | <b>77-1185-79x</b> |
| LSQ3 CCC COMPACT IoT  | <b>77-1184-79x</b> |

### Please note:

Various field bus types available. Please enter the number you require in place of the x:  
1 = EtherNet/IP | 2 = Profinet CU | 3 = EtherCAT



### Accessories: Wall mount for LSQ5

Space-saving design that makes for easy cleaning/maintenance.

## Wall mount

| Overview of wall mounts                           | Part-No.          |
|---------------------------------------------------|-------------------|
| Wall mount for power source LSQ5 and LSQ5 COMPACT | <b>77-1180-01</b> |
| Wall mount for power source LSQ3 and LSQ3 COMPACT | <b>integrated</b> |

## 1 Power source



LSQ5 power source

### LSQ5 power source with Direct Control Technology (DCT)

The LSQ5 ensures the optimum arc energy. It uniquely adjusts to different weld processes. Unlike conventional power sources with inverter technology, the LSQ5 with Direct Control Technology controls its switching transistors without any fixed clock frequency according to the needs of the weld process. Without any delay, the energy needed for the process is provided instantly. The flexible fine tuning is done by a central processor. The CPU continuously analyzes the weld process and current/voltage values on the basis of data obtained and optimally drives the switching transistors of the power section. This results in an extremely high efficiency and a low temperature development.

The power source can be configured with only two buttons and four LED indicators. For worldwide usage, voltages can be configured without opening the power source.



LSQ3 power source

### LSQ3 power source with Direct Control Technology (DCT)

The LSQ3 offers enough power reserves for special weld tasks like chassis and exhaust parts and other thin sheet metal applications.

| Overview of power sources                           | Part-No.   |
|-----------------------------------------------------|------------|
| DCT power source LSQ5 Direct-Control-Technology     | 77-1185-00 |
| DCT power source LSQ3 Direct-Control-Technology     | 77-1184-50 |
| DCT power source LSQ5-CCC Direct-Control-Technology | 77-1185-60 |
| DCT power source LSQ3-CCC Direct-Control-Technology | 77-1184-40 |

#### The main benefits are:

- DCT provides a speed regulation up to ten times higher compared to conventional inverter technology. This leads to excellent control behavior and shorter response times.
- The weld properties are substantially improved. Software replaces hardware: Fewer components also increase the reliability in continuous operation.

| Specifications          | LSQ5 (-CCC)                                                                                            | LSQ3 (-CCC)                  |
|-------------------------|--------------------------------------------------------------------------------------------------------|------------------------------|
| Performance             | 420 A - 60% duty cycle/40 °C (400 A)                                                                   | 340 A - 60% duty cycle/40 °C |
| Processes and functions | GMAW, I-pulse, KF-pulse, microMIG*, microMIG-cc*, MMT-x*, DP-Fast, MIG-Brazing, Synchronweld, AutoComp |                              |
| Weight                  | 49 kg                                                                                                  | 37 kg                        |
| Primary voltage         | 3 x 400 (480) V                                                                                        |                              |
| Wall mounting           | Yes (optional)                                                                                         | Yes (integrated)             |
| Conformities            | CE, CSA, UL (CCC)                                                                                      | CE (CCC)                     |
| Dimensions              | 450 x 400 x 540 mm                                                                                     | 450 x 330 x 540 mm           |

\* Only in combination with Frontpull torch system. Further information can be found in the Frontpull Weld Package.

## 2 Weld process controller

# Innovative Control Concepts with Touch Screen.

With the new Q84r and the compact Q84s up to four weld machines can be controlled centrally.


- **Parameter settings** completely integrated in the SKS software
- **Documentation** of measurements + TCP speed

- ✓ All settings on a single screen
- ✓ All measurements on a single screen
- ✓ All SKS welding processes and functions available
- ✓ Ready to use Industry 4.0 protocols (MQTT + OPC UA) and data traceability!





## 2 Weld process controller



Controlling up to four weld machines at the same time

The new Q84r and Q84s are equipped with a touch screen, an innovative usability concept and an advanced visualization technology for much easier operating. The user interfaces have the look and feel of the Q8Tool4 software. Individual weld process controllers are in card slots in the Q84r/s. This new weld process controller concept can host up to four weld process controller cards. Each card independently controls a weld machine. As an alternative to the Q84r/s weld process controllers, the Q80 has been developed to control a single weld machine.

## 2 Weld process controller



Q84r weld process controller



Q84r Weld process controller

### Please note:

The Q84r/s can be equipped with up to four weld process controller cards.

### Weld process controller Q84r/s

The universal weld process controllers Q84r and Q84s calculate the optimal parameters for each welding process. Only basic data such as material, wire type, wire feed speed and type of gas must be entered. The Q84r is equipped with a 10" touch screen, the space-saving Q84s with a 7" touch screen. For wall mounting the display of the Q84s can be rotated by an angle of 180°.

- Processes and functions: GMAW, I-pulse, KF-pulse, microMIG\*, microMIG-cc\*, MMT-x\*, DP-Fast, MIG Brazing, Synchroweld, AutoComp
- Programs: 15.872 (x4)
- General functions: Display and saving of readings, alarms
- Monitoring functions: Weld current monitoring, auto compensation, arc and ignition monitoring, motor current, gas and water monitoring
- Easy to network via Ethernet: Traceability
- Ports: RJ45-Ethernet, SPW-Bus, SD card slot
- Remote Control/Administration: Q8Tool, VNC client
- Supports MQTT / OPC UA

| Overview weld process controllers                    | Part-No.(Q84s)     | Part-No. (Q84r)    |
|------------------------------------------------------|--------------------|--------------------|
| Q84s/r weld process controller with one weld card    | <b>77-7410-001</b> | <b>77-7310-001</b> |
| Q84s/r weld process controller with two weld cards   | <b>77-7420-001</b> | <b>77-7320-001</b> |
| Q84s/r weld process controller with three weld cards | <b>77-7430-001</b> | <b>77-7330-001</b> |
| Q84s/r weld process controller with four weld cards  | <b>77-7440-001</b> | <b>77-7340-001</b> |

| Overview Q84r/s mounting kits                                        | Part-No.          |
|----------------------------------------------------------------------|-------------------|
| Bracket for Q84r for mounting onto power source LSQ3/5               | <b>77-7240-01</b> |
| Mounting brackets for Q80/Q84s for mounting onto power source LSQ3/5 | <b>77-7240-06</b> |
| Bracket for Q84r for wall mounting                                   | <b>77-7240-02</b> |
| Bracket for Q84r mounting in the robot cabinet                       | <b>77-7240-05</b> |

| Overview Q84r/s accessories                             | Part-No.          |
|---------------------------------------------------------|-------------------|
| Connection cable for Q84r/s 5m with open end (optional) | <b>77-3305-00</b> |
| Plug for external power supply of Q84r/s                | <b>77-7240-96</b> |
| USB adapter for SD/microSD cards                        | <b>91-8-1</b>     |

| Overview Q84r/s replacement parts                              | Part-No.          |
|----------------------------------------------------------------|-------------------|
| Touchpen for Q80 / Q84r/s weld process controller (spare part) | <b>77-7240-03</b> |
| SDHC card 8GB for Q84r/Q84s/Q80 weld process controllers       | <b>91-8-6</b>     |

\* Only in combination with Frontpull torch system. Further information can be found in the Frontpull Weld Package.

## 2 Weld process controller



Q80 weld process controller – front view



Q80 weld process controller – back view


### Weld process controller Q80

The Q80 is the alternative to the Q84r/s. It has the same functionality/features as a single weld card of the Q84r/s - optimized for a single weld machine. With the universal Q80 all parameters and values needed for the weld task can be optimally calculated

- Processes/functions/general functions see Q84r/s
- Easy to network via Ethernet: up to traceability
- Ports: RJ45-Ethernet, SPW-Bus, SD card slot
- Wall mounting capability
- Remote Control / Administration: Q8Tool
- Supports MQTT / OPC UA

| Overview weld process controller                                     | Part-No.           |
|----------------------------------------------------------------------|--------------------|
| Q80 weld process controller                                          | <b>77-7260-001</b> |
| Overview Q80 mounting kits                                           | Part-No.           |
| Bracket for mounting onto power source LSQ5                          | <b>77-7240-06</b>  |
| Overview Q80 accessories                                             | Part-No.           |
| USB adapter for SD-/microSD card                                     | <b>91-8-1</b>      |
| Overview Q80 replacement parts                                       | Part-No.           |
| Touchpen for Q80 / Q84r/s weld process controller (replacement part) | <b>77-7240-03</b>  |
| SDHC card 8GB for Q84r/Q84s/Q80 weld process controllers             | <b>91-8-6</b>      |

## 2 Software/IT



### Q8Tool software

The Q8Tool software provides accurate and comprehensive process monitoring. The user can store weld parameters for documentation on a PC and/or administrate them. It offers basic functions such as reading, modifying and documenting of weld parameters. Additionally, new weld parameters can be created and transferred to the universal weld process controllers. The weld data is portable and the installation of further control units on new equipment is easy. Also, the software allows reading and exporting of measurements and alarms. Graphical and numerical recording of measures helps defining and optimizing parameters for new parts. Users have a powerful tool for analyzing and documenting their weld results.

### Network

The weld process controller units can easily be networked via Ethernet ports: Time savings through centralized administration of all controllers within the corporate network. There is a central backup of all welding parameters, management of user rights and access, process monitoring up to traceability. The Q8Tool software is provided free of charge with the weld process controller. No additional hardware or software is required.

---

### 3 Robot interface

---

## Perfect integration.

Interfacing all industrial robot types.



By the use of Fieldbus Interface FB5 the system can be perfectly integrated into existing Fieldbus environments. For analog and digital environments the universal interface UNI5 is available on request.

---

#### Standard application

---

Fieldbus systems exchange signals via serial communication. The Fieldbus master, usually the robot controller or overall system controller, bundles and processes the signals of the connected Fieldbus, including the welding machine. Standard Fieldbus systems are e.g., Interbus-S, Profibus DP or DeviceNet.

The Fieldbus interface FB5 translates the Fieldbus signals for the welding machine using a standardized protocol. It makes no difference which type of Fieldbus system is used. The signals are always at the same place on the Fieldbus. This makes the preparation of the robot or system controller much easier.

### 3 Robot interface



FB5 Fieldbus Interface: mounting onto the power source



FB5 Fieldbus Interface: mounting onto the cabinet

#### Fieldbus application

Various Fieldbus types are supported (e.g. Profibus DP, DeviceNet). The Fieldbus interface has drilled bore holes for flexible mounting within the weld cell. Two additional mounting kits provide easy installation at the power source or into the cabinet. Additionally, external power can be connected to the interface. More details on solutions for the specific Fieldbus types are available on request.

| Overview FB5 interfaces                           | Part-No. |
|---------------------------------------------------|----------|
| Fieldbus interface FB5 Interbus-S (copper line)   | 77-3-1   |
| Fieldbus interface FB5 Profibus DP                | 77-3-2   |
| Fieldbus interface FB5 DeviceNet                  | 77-3-3   |
| Fieldbus interface FB5 EtherCAT                   | 77-3-4   |
| Fieldbus interface FB5 Profinet IRT (copper line) | 77-3-5   |
| Fieldbus interface FB5 Profinet IRT (LWL 2 Port)  | 77-3-6   |
| Fieldbus interface FB5 Interbus-S (LWL FSMA)      | 77-3-7   |
| Fieldbus interface FB5 Ethernet/IP                | 77-3-8   |

| Cabinet mounting                                       | Part-No.   |
|--------------------------------------------------------|------------|
| Mounting kit for cabinet                               | 77-1182-02 |
| Cabinet cable 2m FB5 with device plug and cable socket | 77-3102-02 |

| Power source mounting                         | Part-No.   |
|-----------------------------------------------|------------|
| Bracket for FB5/Q6pw for mounting onto LSQ3/5 | 77-1182-03 |

| Optional power supply (24V)            | Part-No.   |
|----------------------------------------|------------|
| Connection cable 2.0 m (with open end) | 77-1182-04 |

## SYNCHROWELD

Synchroweld unites the weld system and robot by a communication protocol (RWDE). This technology allows the weld system to get the actual robot speed and automatically adjusts the weld parameters and laser power within defined limits. The result is a constant energy per unit length. At the same time, the programming effort can be significantly reduced.

#### Please note:

Further information on Synchroweld with ABB, Fanuc, KUKA, Yaskawa can be found in our Synchroweld brochure.

## 4 Wire Feeder

# Strong, lightweight and precise.

The PF6 wire feeder.

Smaller and with less weight accompanied by improved efficiency over conventional wire feeders the PF6 goes along with the steady development of arc welding robots.



### Power Feeder PF6

The industrially proven wire feeder PF6 has been enhanced with an additional control and monitoring function - an integrated gas regulation system in addition to the gas flow sensor. The ability to regulate gas flow for the actual weld seam is a crucial factor for seam quality. This also leads to cost savings, as only the amount of gas currently required is passed through the torch system. The proven gas flow sensor, used to monitor the flow rate, is also implemented in this wire feeder variant. Especially with complex components, not having the required gas flow rate can result in high costs, as the component may become unusable - in the best case, it can only be salvaged through extensive rework. The target and actual gas quantities can be read on the welding process control system. Additionally, an alarm can be triggered if the values fall below or exceed the set limits.

| Overview PF6                                   | Part-No.       |
|------------------------------------------------|----------------|
| PF6 wire feeder                                | 10-3-8         |
| PF6 wire feeder with integrated gas regulation | 10-3-508       |
| Specifications                                 |                |
| Weight                                         | 4.1 kg         |
| Motor                                          | 70 W           |
| Wire feeding speed [v]                         | 2.5 - 25 m/min |
| Drive roll for wire diameter                   | 0.8 - 1.6 mm   |



### Center guide

The center guide ensures a defined routing of the welding wire within the four roll drive.

| Overview center guide                                                  | Part-No.  |
|------------------------------------------------------------------------|-----------|
| Center guide for PF5/6 wire feeder, wire-ø 0.8 - 1.6 mm for steel wire | 12-2-1-15 |

## 4 Wire Feeder



### Please note:

Two drive rolls per system are needed.

### Please note:

Drive rolls for wires in inch sizes available on request.

### Drive roll

Our drive rolls are available in several groove shapes for different welding filler materials (V-groove for steel and knurled U-groove for filler wire applications).

| Overview drive rolls                 | Part-No.         |
|--------------------------------------|------------------|
| Wire- $\varnothing$ 0.8 mm, V-groove | <b>12-2-4-08</b> |
| Wire- $\varnothing$ 0.9 mm, V-groove | <b>12-2-4-09</b> |
| Wire- $\varnothing$ 1.0 mm, V-groove | <b>12-2-4-10</b> |
| Wire- $\varnothing$ 1.2 mm, V-groove | <b>12-2-4-12</b> |
| Wire- $\varnothing$ 1.4 mm, V-groove | <b>12-2-4-14</b> |
| Wire- $\varnothing$ 1.6 mm, V-groove | <b>12-2-4-16</b> |

| Overview drive rolls                        | Part-No.          |
|---------------------------------------------|-------------------|
| Filler Wire- $\varnothing$ 1.0 mm, U-groove | <b>12-2-4-310</b> |
| Filler Wire- $\varnothing$ 1.2 mm, U-groove | <b>12-2-4-312</b> |
| Filler Wire- $\varnothing$ 1.6 mm, U-groove | <b>12-2-4-316</b> |



### Please note:

Two pressure rolls and two locating bolts are needed per system.

### Pressure roll

The pressure roll ensures a defined pressure of the welding wire into the specific groove shape of the drive roll.

| Overview pressure rolls                                  | Part-No.        |
|----------------------------------------------------------|-----------------|
| Pressure roll – DIN 625 T1 for PF5/6 wire feeder series  | <b>12-2-3-0</b> |
| Locating bolt for pressure roll on two/four roller drive | <b>12-13-5</b>  |



### Please note:

Wire feeder brackets for further robot types are available on request.

### Wire feeder bracket

Wire feeder bracket with holes and mounting material for quick and easy installation.

| Overview wire feeder brackets                | Part-No.       |
|----------------------------------------------|----------------|
| <b>For robot type-ABB (single wire)</b>      |                |
| IRB 1600-6/1.2                               | <b>14-12-3</b> |
| IRB 2400-10/1.55                             | <b>14-2-4</b>  |
| IRB 2600-12/1.85                             | <b>14-2-7</b>  |
| <b>For robot type-FANUC (single wire)</b>    |                |
| AM 100iD / AM 120iD / M-10iD/8L / M-20iD/12L | <b>14-4-2</b>  |

### For robot type-KUKA (single wire)


|                                        |               |
|----------------------------------------|---------------|
| KR 8 R1620 / KR 10 R1420 / KR 12 R1810 | <b>14-3-2</b> |
|----------------------------------------|---------------|

### For robot type-YASKAWA (single wire)

|                 |                |
|-----------------|----------------|
| AR 1440 / GP 12 | <b>14-1-26</b> |
| AR 2010         | <b>14-1-16</b> |



## 5 FlexiGlide wire guidance



- 1 Wire inlet body for PF5/6 with quick coupling
- 2 Connection Nipple for FlexiGlide with tension spring
- 3 FlexiGlide Wire Guidance
- 4 Connection Nipple for FlexiGlide without tension spring
- 5 Drum connector with ceramic inlay



FlexiGlide Wire Guidance

### Please note:

Further information can be found in our brochures "FlexiGlide" (PIN-0168) and "Wire guidance" (DOC-0193).

SKS Wire guidance FlexiGlide with a high limit of elasticity and very low friction. The constructive design, a coil made from chrome/nickel spring steel with a plastic coating, creates robustness, resulting in a high lifetime.

### Benefits with FlexiGlide:

- Optimized for use in robotic applications
- High lifetime
- Very low friction
- Flame retardant and abrasion resistant

### FlexiGlide wire guidance


| Overview of FlexiGlide wire guidance                           | Part-No.  |
|----------------------------------------------------------------|-----------|
| Wire Inlet Body for PF5/6 with Quick-Connector                 | 10-2-0-61 |
| Connection Nipple insulated for FlexiGlide with tension spring | 44-3-11   |
| FlexiGlide wire guidance, Type B, per meter                    | 44-3-1    |
| Connection Nipple for FlexiGlide without tension spring        | 44-3-4    |
| Drum Connector with ceramic inlet                              | 44-40-1   |

### Option

| Overview strain-relief on wire guidance                          | Part-No. |
|------------------------------------------------------------------|----------|
| Strain-relief for wire guidance on wire feeder bracket           | 14-10-6  |
| Through-Wall Mount for wire guidance FlexiGlide incl. suspension | 44-3-8   |
| Wall Duct for FlexiGlide wire guidance                           | 44-3-9   |



## 5 Rolliner 3G wire guidance



- 1 Wire inlet body for PF5/6 with inner thread
- 2 Connection set Rolliner NG
- 3 Connector wire outlet
- 4 Wire Guidance Rolliner 3G in corrugated tube black NW23
- 5 Connector wire inlet
- 6 Wire drum connector for Rolliner

Rolliner 3G Wire guidance is suitable for all applications where higher wire feeding requirements are needed.

### Benefits:

- Optimized sliding properties with roller-supported wire guidance
- High flexibility due to segmentation of roller parts
- Suitable for use in harsh environments
- Universally application (steel, stainless steel, filler wire, aluminum)

| Overview of Rolliner 3G wire guidance                 | Part-No.  |
|-------------------------------------------------------|-----------|
| Wire inlet body for PF5/6 with 1/4" NPTF inner thread | 10-2-0-60 |
| Connection set Rolliner NG for drum or wire feeder    | 44-60-21  |
| Connector wire outlet for Rolliner 3G                 | 44-60-42  |
| Mounting clip for Rolliner 3G                         | 44-60-45  |
| Wire Guidance Rolliner 3G per meter                   | 44-60-40  |
| Corrugated tube PUR black NW23 per meter              | 91-3-2    |
| Connector wire inlet for Rolliner 3G                  | 44-60-41  |
| Wire drum connector for Rolliner NG                   | 44-60-30  |

### Option

| Overview of strain-relief on wire guidance     | Part-No. |
|------------------------------------------------|----------|
| Strain-relief wire guidance for Rolliner       | 14-10-8  |
| Clamping Piece Rolliner 3G on Cable Bundle -A- | 44-60-48 |

### Please note:

Two connection sets are needed.

### Alternative



### Wire inlet bodies for additional systems

Beside the wire inlet body for the SKS wire guidance, inlet bodies for additional systems are available.

| Overview of wire inlet bodies for additional systems        | Part-No.  |
|-------------------------------------------------------------|-----------|
| Wire inlet body for PF5/6 with M10 internal thread for ESAB | 10-2-0-50 |
| Wire inlet body for PF5/6 with 9.6 mm bore hole             | 10-2-0-52 |
| Wire inlet body for PF5/6 with 13 mm bore hole              | 10-2-0-53 |
| Wire inlet body for PF5/6 with PG9 thread                   | 10-2-0-56 |
| Wire inlet body for PF5/6 with internal thread 1/4" NPTF    | 10-2-0-60 |

## 6 Ground cable



### Please note:

Further lengths and diameters available on request

### Ground cable with 70 mm<sup>2</sup> connector and cable lug

The use of highly pure copper reduces the electric resistance supporting the welding process. Manufactured as of DIN VDE 0285-525-2-81 / DIN EN 50525-2-81.

| Overview of ground cables                                        | Part-No.         |
|------------------------------------------------------------------|------------------|
| Ground cable 70 mm <sup>2</sup> 6 m with DIX plug and cable lug  | <b>228078106</b> |
| Ground cable 70 mm <sup>2</sup> 10 m with DIX plug and cable lug | <b>228078100</b> |

### Option

| Overview of ground cables                                        | Part-No.         |
|------------------------------------------------------------------|------------------|
| Ground cable 95 mm <sup>2</sup> 6 m with DIX plug and cable lug  | <b>228080106</b> |
| Ground cable 95 mm <sup>2</sup> 10 m with DIX plug and cable lug | <b>228080110</b> |

## 7 Control cable



### Please note:

For the Frontpull 8 system three control cables are needed. One control cable is already included in the cable bundle.

### Please note:

Further lengths available on request.

### Control cable: L700/SPW-Bus

One cable to connect power source, weld process controller, interface and frontpull module. By use of one cable stock and installation is simplified. The power is supplied via this cable. An external supply is not necessary.

| Overview of control cables      | Part-No.         |
|---------------------------------|------------------|
| Control cable 0.5m L700/SPW-Bus | <b>541031050</b> |
| Control cable 1m L700/SPW-Bus   | <b>541031001</b> |
| Control cable 2m L700/SPW-Bus   | <b>541031002</b> |
| Control cable 3m L700/SPW-Bus   | <b>541031003</b> |
| Control cable 5m L700/SPW-Bus   | <b>541031005</b> |
| Control cable 7m L700/SPW-Bus   | <b>541031007</b> |
| Control cable 10m L700/SPW-Bus  | <b>541031000</b> |
| Control cable 12m L700/SPW-Bus  | <b>541031012</b> |
| Control cable 15m L700/SPW-Bus  | <b>541031015</b> |

### Plug & Play: Control cable L700

The advantages of a system concept are revealed by its details: One standard control cable (L700) connects all system components (power source, robot interface, weld process controller and wire feeder) within the welding system. The system is expandable: Other components can be integrated at any time into an existing system. New devices are automatically detected.



Power Source



Robot Interface



Weld Process Controller



Wire Feeder

## 8 Cable bundle



### Cable bundles: Power source to PF6

Coaxial power cable 72 mm<sup>2</sup> with internal gas flow, control cable L700, disconnect cable, corrugated tube and cable holder. Air-cooled version.

| Overview of cable bundles                        | Part-No. |
|--------------------------------------------------|----------|
| Cable bundle 72mm <sup>2</sup> 5m -A- LSQ-PF5/6  | 20-4-5   |
| Cable bundle 72mm <sup>2</sup> 7m -A- LSQ-PF5/6  | 20-4-7   |
| Cable bundle 72mm <sup>2</sup> 10m -A- LSQ-PF5/6 | 20-4-10  |


### Alternative

| Overview of cable bundles with air-blast function                        | Part-No. |
|--------------------------------------------------------------------------|----------|
| Cable bundle 72mm <sup>2</sup> 5m -A- LSQ-PF5/6 with air-blast function  | 20-19-5  |
| Cable bundle 72mm <sup>2</sup> 7m -A- LSQ-PF5/6 with air-blast function  | 20-19-7  |
| Cable bundle 72mm <sup>2</sup> 10m -A- LSQ-PF5/6 with air-blast function | 20-19-10 |
| Air blast valve for mounting on the wire feeder bracket                  | 93-50    |

#### Please note:

Further lengths available on request.

## 8 Cable bundle: Clamping set



### Mounting cable bundle: clamping set -A-

Provides perfect installation of the cable bundle for all different robot types. Undesired cable movements are prevented. This results in higher lifetime.

| Overview of clamping sets   | Part-No.                                | For robot type-KUKA           |
|-----------------------------|-----------------------------------------|-------------------------------|
| <b>For robot type-ABB</b>   |                                         | KR 8 R1620 / KR 10 R1420      |
| IRB 1600-6/1.2              | 91-3-0-41-10                            | 91-3-0-41-17                  |
| IRB 2400-10/1.55            | not available                           | KR 12 R1810                   |
| IRB 2600-12/1.85            | 91-3-0-41-11                            | 91-3-0-41-12                  |
| <b>For robot type-FANUC</b> |                                         | <b>For robot type-YASKAWA</b> |
| AM 100iD / AM 120iD         | 91-3-0-41-23<br>(optional 91-3-0-41-30) | AR 1440 / AR 2010 / GP 12     |
| M-10iD/8L / M-20iD/12L      | 91-3-0-41-23<br>(optional 91-3-0-41-30) | 91-3-0-41-22                  |

#### Please note:


Clamping sets for further robot types are available on request.

### Alternative

| Mounting for WF-bracket                                  | Part-No. |
|----------------------------------------------------------|----------|
| Mounting for WF-bracket for external guided cable bundle | 14-10-10 |


## 8 Dividable cable bundles

### Alternative



**70 mm² Connection from power source to connection bracket -A-**

| Length | Part-No. | Part-No.<br>(with air-blast function) |
|--------|----------|---------------------------------------|
| 5 m    | 20-7-5   | 20-21-5                               |
| 7 m    | 20-7-7   | 20-21-7                               |
| 10 m   | 20-7-10  | 20-21-10                              |



**Connection bracket for cable bundles (PF6) -A-**

|                    | Part-No. |
|--------------------|----------|
| Connection bracket | 20-6-0-3 |



**Connection 72 mm² from connection bracket to PF6 -A-**

| Length | Part-No. | Part-No.<br>(with air-blast function) |
|--------|----------|---------------------------------------|
| 3 m    | 20-6-3   | 20-20-3                               |
| 5 m    | 20-6-5   | 20-20-5                               |
| 7 m    | 20-6-7   | 20-20-7                               |

#### Please note:

Further lengths available on request.

#### Please note:

For use of the air blast function the air blast valve (Part-No. 93-50) is required.

### Cable bundle with separation between power source and wire feeder PF6

The moving parts of the cable bundle (next to the robot) are separated from the non-moving parts (power source). In case of maintenance work, only the moving parts have to be changed. The quick and easy replacement concept results in time and cost savings.



## Power Clutch: New precision.

For all industrial robots with outer cable dress.



The Power Clutch torch system perfects the interaction of welding machines and robots with outer cable dress. The SKS Power Clutch torch system consists of the Power Clutch collision protection, a robot-specific mounting flange, the torch cable and the torch neck with consumables. The changing of the torch neck is designed to be tool-free. This allows for a TCP accuracy of  $\pm 0.2$  mm when changing torch necks.

---

### Power Clutch – air-cooled for steel applications


---

|                        |                                           |
|------------------------|-------------------------------------------|
| <b>Processes:</b>      | GMAW, KF-pulse, Pulse, MIG-Brazing        |
| <b>Wire materials:</b> | high-alloy steels, low-alloy steels       |
| <b>Compatibility:</b>  | for all common industrial robots          |
| <b>Weight:</b>         | 2.5 kg                                    |
| <b>Max. power:</b>     | 420 A – 60 % duty cycle/40 °C, air-cooled |
| <b>Wire diameter:</b>  | 0.8-1.6 mm                                |
| <b>TCP accuracy:</b>   | $\pm 0.2$ ( 400 mm)                       |

---

## 9 Torch System Power Clutch: Parts Overview

All parts of the  
Power Clutch torch  
system at a glance.



- 9a Collision Protection 9b Torch Mounting Arm 9c Robot Mounting  
9d Torch Cable and Accessories 10a Torch Neck 10b Consumables 10c Gas Nozzle

## 9 Torch System Power Clutch: Parts Overview





## 9a Torch system: Collision protection



### Collision protection Power Clutch HD for welding robots with outer cable dress

The SKS collision protection is based on the Power Joint concept, continuing the modular structure of the SKS components. This ensures the same high precision TCP accuracy in the Frontpull 8 as found in SKS Power Joint systems. Aside from the industrial proven Power Clutch, an adaptor without collision protection is available. This adaptor has the same component length to maintain modularity and compliance with the TCP.

| Power Clutch 2                          | Part-No.     |
|-----------------------------------------|--------------|
| SKS collision protection Power Clutch 2 | <b>71-17</b> |
| Solid Mount for SKS torch systems       | <b>93-33</b> |

| Technical data Power Clutch 2 |                          |
|-------------------------------|--------------------------|
| Collision protection          | deflection 10°           |
| Reset accuracy                | ± 0.2 mm with TCP 400 mm |
| Weight                        | 1.5 kg                   |



## 9b Brennersystem: Brennerhalter




### Power Clutch: Torch mounting arm

The precise torch mounting arm with air blast connector and proven bayonet quick-change connectors for torch cable and torch neck.

| Overview torch mounting arm             | Part-No.       |
|-----------------------------------------|----------------|
| Power Clutch torch mounting arm 45°/30° | <b>62-5-15</b> |

## 9c Torch system: Robot mounting



### Connection flange Power Clutch

| Overview of connection flanges               | Part-No.       | Insulation flange<br>(when using 93-33) |
|----------------------------------------------|----------------|-----------------------------------------|
| <b>For robot type-ABB</b>                    |                | <b>Part-No.</b>                         |
| IRB 2400-10/1.55 / IRB 2600-12/1.85          | <b>63-4-5</b>  | <b>63-2-5</b>                           |
| IRB 1600-6/1.2                               | <b>63-4-13</b> | <b>63-2-13</b>                          |
| <b>For robot type-FANUC</b>                  |                |                                         |
| AM 100iD / AM 120iD / M-10iD/8L / M-20iD/12L | <b>63-4-24</b> | <b>63-2-24</b>                          |
| <b>For robot type-KUKA</b>                   |                |                                         |
| KR 8 R1620 / KR 10 R1420                     | <b>63-4-16</b> | <b>63-2-16</b>                          |
| KR 12 R1810                                  | <b>63-4-3</b>  | <b>63-2-3</b>                           |
| <b>For robot type-YASKAWA</b>                |                |                                         |
| AR 1440 / AR 2010 / GP 12                    | <b>63-4-8</b>  | <b>63-2-8</b>                           |

#### Please note:

Connection flanges for further cobots are available on request.



## 9d Torch system: Torch cable and accessories



### Please note:

Further lengths of torch cables and liners are available upon request.

### Torch cable with outer cable dress

High flexible coaxial cable 72 mm<sup>2</sup> with air blast tube, disconnection cable and Power Pin

| Overview of recommended torch cable lengths for robots | Part-No.        |
|--------------------------------------------------------|-----------------|
| <b>For robot type-ABB</b>                              |                 |
| IRB 1600-6/1.2                                         | <b>61-5-075</b> |
| IRB 2400-10/1.55                                       | <b>61-5-09</b>  |
| IRB 2600-12/1.85                                       | <b>61-5-10</b>  |
| <b>For robot type-FANUC</b>                            |                 |
| AM 100iD                                               | <b>61-5-09</b>  |
| AM 120iD                                               | <b>61-5-10</b>  |
| M-10iD/8L                                              | <b>61-5-12</b>  |
| M-20iD/12L                                             | <b>61-5-15</b>  |

### For robot type-KUKA

|                          |                |
|--------------------------|----------------|
| KR 8 R1620 / KR 10 R1420 | <b>61-5-09</b> |
| KR 12 R1810              | <b>61-5-11</b> |

### For robot type-YASKAWA

|                 |                |
|-----------------|----------------|
| AR 1440 / GP 12 | <b>61-5-10</b> |
| AR 2010         | <b>61-5-12</b> |

| Overview torch cables | Part-No.        |
|-----------------------|-----------------|
| 0.75 m                | <b>61-5-075</b> |
| 0.9 m                 | <b>61-5-09</b>  |
| 1.0 m                 | <b>61-5-10</b>  |
| 1.1 m                 | <b>61-5-11</b>  |
| 1.2 m                 | <b>61-5-12</b>  |

|       |                |
|-------|----------------|
| 1.5 m | <b>61-5-15</b> |
| 1.8 m | <b>61-5-18</b> |
| 2.0 m | <b>61-5-20</b> |
| 2.4 m | <b>61-5-24</b> |



### Liner

| Overview liners                                    | Part-No.               |
|----------------------------------------------------|------------------------|
| SKS Front Load Liner 2.3m, Wire-ø 0.8–1.0mm, Steel | <b>44-34-10-2350-S</b> |
| SKS Front Load Liner 3.5m, Wire-ø 0.8–1.0mm, Steel | <b>44-34-10-3550-S</b> |
| SKS Front Load Liner 2.3m, Wire-ø 1.2–1.6mm, Steel | <b>44-34-16-2350-S</b> |
| SKS Front Load Liner 3.5m, Wire-ø 1.2–1.6mm, Steel | <b>44-34-16-3550-S</b> |
| Power Pin Cap for SKS Front Load Liner             | <b>61-2-0-2-17</b>     |

**INCLUDING  
STOP'N'LOCK  
FUNCTION**



## The new SKS Front Load Liner

This new liner system will replace the current Quick Load liner system, providing the same installation features and product performance, along with a lower list price.



## Torch necks for Power Clutch

SKS torch necks are available in different geometries and for a wide range of applications. With its innovative bajonet lock system, the SKS torch neck can be replaced quickly. This unique tool-free quick change system is also highly precise with TCP accuracy of  $\pm 0,2$  mm. Their design concept allows them to be used in areas where market standard torch necks would already require water cooling.


| Overview of torch necks      |                |           | Application recommendations |            |
|------------------------------|----------------|-----------|-----------------------------|------------|
| Type                         | Part-No.       | angle [°] | TCP length [mm]             | steel/CrNi |
| standard dressing air-cooled | 58-1-00-400-1  | 0         | 461,5                       | ✓          |
|                              | 58-1-22-350-1  | 22        | 411,5                       | ✓          |
|                              | 58-1-22-400-1  | 22        | 461,5                       | ✓          |
|                              | 58-4-330-500-1 | 30        | 500,0                       | ✓          |
|                              | 58-1-130-450-1 | 30        | 511,5                       | ✓          |
|                              | 58-1-35-400-1  | 35        | 461,5                       | ✓          |
|                              | 58-1-45-350-1  | 45        | 411,5                       | ✓          |
|                              | 58-1-45-400-1  | 45        | 461,5                       | ✓          |
|                              | 58-1-45-450-1  | 45        | 511,5                       | ✓          |
|                              | 58-4-345-450-1 | 45        | 450,0                       | ✓ ✓        |
|                              | 58-4-345-567-1 | 45        | 567,0                       | ✓          |

| Type | Part-No.       | angle [°] | TCP length [mm] | steel/CrNi |
|------|----------------|-----------|-----------------|------------|
| ZK   | 58-1-245-400-1 | 45        | 461,5           | ✓          |

- ✓ ✓ Recommended standard torch neck
- ✓ Recommended

### Please note:

For information about aluminum application please see our brochures "Frontpull 8 Aluminum".



### Info: Torch Neck

SKS offers a special torch neck (up to 250 A, ZK-HeavyDuty up to max. 300 A) for welding components with tight accessibility. The special torch neck needs a smaller insulator (ZK) and a more compact gas nozzle (ZK). Standard Power Lock contact tips can be used. TCP drawings can be found on the next to last page (torch necks).



### Clamping cap for SKS single wire torch necks

Tool-free assembly with bayonet quick-change system

| Clamping cap | Part-No. |
|--------------|----------|
| Clamping cap | 71-3-25  |



### Isolator für SKS Brennerhalse


| Overview of insulators     | Part-No. |
|----------------------------|----------|
| Torch neck insulator       | 58-1-5   |
| Torch neck insulator ZK-HD | 43-6-4-3 |



## 10a Torch necks

### Torch neck change with the SKS bayonet locking concept

Find an interactive animation of how it works in the QR code



**Please note:**

Animation using the example of a standard torch neck in the Power Joint Weld Package.

## 10b Consumables



**Please note:**

An overview with dimensions can be found on the page after next.

### Power Lock Plus: retaining head

Heavy duty retaining head with thread for threaded gas nozzles for simple and safe installation

| Overview of retaining heads                              | Part-No. |
|----------------------------------------------------------|----------|
| Heavy duty retaining head Power Lock Plus (6 holes)      | 43-16-6  |
| Heavy duty retaining head Power Lock Plus - ZK (6 holes) | 43-24-1  |

## 10b Consumables



### Please note:

Contact tips for wires in inch sizes available on request.

### Power Lock Plus: Contact tip

- Tapered design for high TCP reproducibility
- Improved heat transfer extends lifetime
- Improved power transition: constant arc quality

| Overview of contact tips                                              | Part-No.    |
|-----------------------------------------------------------------------|-------------|
| Contact tip Power Lock Plus for wire- $\varnothing$ 0.8 mm, E-Cu      | 40-6-5-0.8E |
| Contact tip Power Lock Plus for wire- $\varnothing$ 0.9 mm, E-Cu      | 40-6-5-0.9E |
| Contact tip Power Lock Plus for wire- $\varnothing$ 1.0 mm, E-Cu      | 40-6-5-1.0E |
| Contact tip Power Lock Plus for wire- $\varnothing$ 1.2 mm, E-Cu      | 40-6-5-1.2E |
| Contact tip Power Lock Plus for wire- $\varnothing$ 0.8 mm, HD-CuCrZr | 40-6-7-0.8S |
| Contact tip Power Lock Plus for wire- $\varnothing$ 0.9 mm, HD-CuCrZr | 40-6-7-0.9S |
| Contact tip Power Lock Plus for wire- $\varnothing$ 1.0 mm, HD-CuCrZr | 40-6-7-1.0S |
| Contact tip Power Lock Plus for wire- $\varnothing$ 1.2 mm, HD-CuCrZr | 40-6-7-1.2S |
| Contact tip Power Lock Plus for wire- $\varnothing$ 1.4 mm, HD-CuCrZr | 40-6-7-1.4S |
| Contact tip Power Lock Plus for wire- $\varnothing$ 1.6 mm, HD-CuCrZr | 40-6-7-1.6S |

## 10c Gas nozzle



### Please note:

An overview with dimensions can be found on the next page.

### Please note:

Further information can be found in our brochure "Consumables" (DOC-0135EN).

### Gas nozzles with thread

| Standard gas nozzles       | Part-No.    |
|----------------------------|-------------|
| <b>13 mm bottle shaped</b> |             |
| short                      | 41-19-13-BS |
| flush                      | 41-19-13-BF |
| long                       | 41-19-13-BR |
| <b>13 mm tapered</b>       |             |
| short                      | 41-19-13-TS |
| flush                      | 41-19-13-TF |
| long                       | 41-19-13-TR |
| <b>15 mm bottle shaped</b> |             |
| short                      | 41-19-15-BS |
| flush                      | 41-19-15-BF |
| long                       | 41-19-15-BR |
| <b>16 mm tapered</b>       |             |
| short                      | 41-19-16-TS |
| flush                      | 41-19-16-TF |
| long                       | 41-19-16-TR |

| Heavy Duty gas nozzles | Part-No.    |
|------------------------|-------------|
| <b>13 mm</b>           |             |
| flush, bottle shaped   | 41-20-13-BF |
| long, tapered          | 41-20-13-TR |
| <b>16 mm tapered</b>   |             |
| kurz                   | 41-20-16-TS |
| flush                  | 41-20-16-TF |
| long                   | 41-20-16-TR |

| ZK type gas nozzles                | Part-No.    |
|------------------------------------|-------------|
| <b>13 mm bottle shaped</b>         |             |
| short                              | 41-21-13-BS |
| flush                              | 41-21-13-BF |
| <b>15 mm bottle shaped</b>         |             |
| short                              | 41-21-15-BS |
| flush                              | 41-21-15-BF |
| <b>13+15 mm Heavy Duty/tapered</b> |             |
| 13 mm flush                        | 41-22-13-TF |
| 15 mm flush                        | 41-22-15-TF |



### Tools and accessories

For replacement of contact tips: Fast exchange of contact tip without removing the gas nozzle

| Overview of tools and accessories                   | Part-No.   |
|-----------------------------------------------------|------------|
| Mounting tool SW7 for contact tip (Power Lock Plus) | 51-9002-00 |
| Stopper-Key for drive rolls (Std & Lite)            | 93-100-3-3 |
| SKS Multitool for single wire torch systems         | 47-11      |

### Programming tips


Programming tips for precise seam programming

| Overview of programming tips | Part-No. |
|------------------------------|----------|
| <b>Stickout</b>              |          |
| 15 mm (Power Lock Plus)      | 65-11    |
| 15 mm (Power Lock Plus)      | 65-12    |




# 10c Gas nozzles: Overview dimensions

## 13 mm bottle-shaped




|                                                              |             |             |             |
|--------------------------------------------------------------|-------------|-------------|-------------|
| Gas nozzle Part-No.                                          | 41-19-13-BS | 41-19-13-BF | 41-19-13-BR |
| Reamer Blade:<br>Power Lock Plus<br>(UNF 3/8" x 24) Part-No. | 82-2-1-13-S | 82-2-1-13-F | 82-2-1-13-R |
| (M10 x 1) eReam 2.0 Part-No.                                 | 82-2-2-13-S | 82-2-2-13-F | 82-2-2-13-R |

## 13 mm tapered




|             |             |             |
|-------------|-------------|-------------|
| 41-19-13-TS | 41-19-13-TF | 41-19-13-TR |
| 82-2-1-13-S | 82-2-1-13-F | 82-2-1-13-R |
| 82-2-2-13-S | 82-2-2-13-F | 82-2-2-13-R |

## 13 mm Heavy Duty




|             |             |
|-------------|-------------|
| 41-20-13-BF | 41-20-13-TR |
| 82-2-1-13-F | 82-2-1-13-R |
| 82-2-2-13-F | 82-2-2-13-R |

## 15 mm bottle-shaped




|                                                              |             |             |             |
|--------------------------------------------------------------|-------------|-------------|-------------|
| Gas nozzle Part-No.                                          | 41-19-15-BS | 41-19-15-BF | 41-19-15-BR |
| Reamer Blade:<br>Power Lock Plus<br>(UNF 3/8" x 24) Part-No. | 82-2-1-15-S | 82-2-1-15-F | 82-2-1-15-R |
| (M10 x 1) eReam 2.0 Part-No.                                 | 82-2-2-15-S | 82-2-2-15-F | 82-2-2-15-R |

## 16 mm tapered



|             |             |             |
|-------------|-------------|-------------|
| 41-19-16-TS | 41-19-16-TF | 41-19-16-TR |
| 82-2-1-16-S | 82-2-1-16-F | 82-2-1-16-R |
| 82-2-2-16-S | 82-2-2-16-F | 82-2-2-16-R |


## 16 mm Heavy Duty



|             |             |             |
|-------------|-------------|-------------|
| 41-20-16-TS | 41-20-16-TF | 41-20-16-TR |
| 82-2-1-16-S | 82-2-1-16-F | 82-2-1-16-R |
| 82-2-2-16-S | 82-2-2-16-F | 82-2-2-16-R |


## ZK type:

### 13 mm bottle-shaped




|                                                              |             |             |
|--------------------------------------------------------------|-------------|-------------|
| Gas nozzle Part-No.                                          | 41-21-13-BS | 41-21-13-BF |
| Reamer Blade:<br>Power Lock Plus<br>(UNF 3/8" x 24) Part-No. | 82-6-1-13-S | 82-6-1-13-F |
| (M10 x 1) eReam 2.0 Part-No.                                 | 82-6-2-13-S | 82-6-2-13-F |

### 15 mm bottle-shaped



|             |             |
|-------------|-------------|
| 41-21-15-BS | 41-21-15-BF |
| 82-6-1-15-S | 82-6-1-15-F |
| 82-6-2-15-S | 82-6-2-15-F |

### 13+15 mm Heavy Duty/tapered



|             |             |
|-------------|-------------|
| 41-22-13-TF | 41-22-15-TF |
| 82-6-1-13-F | 82-6-1-15-F |
| 82-6-2-13-F | 82-6-2-15-F |


### Please note:

Further gas nozzles, reamer blades and torch necks can be found in our consumables brochure.

### Please note:

Dimensions in mm.

## 11 Reamer blades




### Reamer blade (internal thread UNF 3/8" x 24)

For pReam cleaning station

| Overview of reamer blades        | Part-No.    | Part-No.    | Part-No.    |
|----------------------------------|-------------|-------------|-------------|
| Inner diameter of the gas nozzle | short       | flush       | long        |
| 13 mm                            | 82-2-1-13-S | 82-2-1-13-F | 82-2-1-13-R |
| 15 mm                            | 82-2-1-15-S | 82-2-1-15-F | 82-2-1-15-R |
| 16 mm                            | 82-2-1-16-S | 82-2-1-16-F | 82-2-1-16-R |

| Dimensions                  |    |    |      |      |   | Part-No.    |
|-----------------------------|----|----|------|------|---|-------------|
| A                           | B  | C  | D    | E    | F |             |
| <b>13 mm inner diameter</b> |    |    |      |      |   |             |
| 55.5                        | -  | 67 | 12.5 | 9    | - | 82-2-1-13-S |
| 52.5                        | -  | 67 | 12.5 | 9    | - | 82-2-1-13-F |
| 49.5                        | -  | 67 | 12.5 | 9    | - | 82-2-1-13-R |
| <b>15 mm inner diameter</b> |    |    |      |      |   |             |
| 51                          | 63 | 91 | 14.5 | 11.8 | 9 | 82-2-1-15-S |
| 48                          | 63 | 91 | 14.5 | 11.8 | 9 | 82-2-1-15-F |
| 45                          | 63 | 91 | 14.5 | 11.8 | 9 | 82-2-1-15-R |
| <b>16 mm inner diameter</b> |    |    |      |      |   |             |
| 51                          | 63 | 91 | 15.5 | 11.8 | 9 | 82-2-1-16-S |
| 48                          | 63 | 91 | 15.5 | 11.8 | 9 | 82-2-1-16-F |
| 45                          | 63 | 91 | 15.5 | 11.8 | 9 | 82-2-1-16-R |



### Reamer blade (internal thread M10 x 1)

For eReam 2.0 cleaning station


| Overview of reamer blades        | Part-No.    | Part-No.    | Part-No.    |
|----------------------------------|-------------|-------------|-------------|
| Inner diameter of the gas nozzle | short       | flush       | long        |
| 13 mm                            | 82-2-2-13-S | 82-2-2-13-F | 82-2-2-13-R |
| 15 mm                            | 82-2-2-15-S | 82-2-2-15-F | 82-2-2-15-R |
| 16 mm                            | 82-2-2-16-S | 82-2-2-16-F | 82-2-2-16-R |

| Dimensions                  |    |    |      |      |   | Part-No.    |
|-----------------------------|----|----|------|------|---|-------------|
| A                           | B  | C  | D    | E    | F |             |
| <b>13 mm inner diameter</b> |    |    |      |      |   |             |
| 66.5                        | -  | 78 | 12.5 | 9    | - | 82-2-2-13-S |
| 66.5                        | -  | 81 | 12.5 | 9    | - | 82-2-2-13-F |
| 66.5                        | -  | 84 | 12.5 | 9    | - | 82-2-2-13-R |
| <b>15 mm inner diameter</b> |    |    |      |      |   |             |
| 38                          | 50 | 78 | 14.5 | 11.8 | 9 | 82-2-2-15-S |
| 38                          | 53 | 81 | 14.5 | 11.8 | 9 | 82-2-2-15-F |
| 38                          | 56 | 84 | 14.5 | 11.8 | 9 | 82-2-2-15-R |
| <b>16 mm inner diameter</b> |    |    |      |      |   |             |
| 38                          | 50 | 78 | 15.5 | 11.8 | 9 | 82-2-2-16-S |
| 38                          | 53 | 81 | 15.5 | 11.8 | 9 | 82-2-2-16-F |
| 38                          | 56 | 84 | 15.5 | 11.8 | 9 | 82-2-2-16-R |

#### Please note:

Dimensions in mm.

## 11 Reamer blades: ZK type




### Reamer blade ZK series Power Lock Plus (internal thread UNF 3/8" x 24)

For pReam cleaning station

| Overview of reamer blades        | Part-No.    | Part-No.    | Part-No. |
|----------------------------------|-------------|-------------|----------|
| Inner diameter of the gas nozzle | short       | flush       | long     |
| 13 mm                            | 82-6-1-13-S | 82-6-1-13-F | -        |
| 15 mm                            | 82-6-1-15-S | 82-6-1-15-F | -        |

| Dimensions                  |   |    |      |      |   | Part-No.    |
|-----------------------------|---|----|------|------|---|-------------|
| A                           | B | C  | D    | E    | F |             |
| <b>13 mm inner diameter</b> |   |    |      |      |   |             |
| 45                          | - | 77 | 12.5 | 11.8 | 9 | 82-6-1-13-S |
| 42                          | - | 77 | 12.5 | 11.8 | 9 | 82-6-1-13-F |
| <b>15 mm inner diameter</b> |   |    |      |      |   |             |
| 45                          | - | 77 | 14.5 | 11.8 | 9 | 82-6-1-15-S |
| 42                          | - | 77 | 14.5 | 11.8 | 9 | 82-6-1-15-F |



### Reamer blade ZK series Power Lock Plus (internal thread M10 x 1)

For eReam 2.0 cleaning station

| Overview of reamer blades        | Part-No.    | Part-No.    | Part-No. |
|----------------------------------|-------------|-------------|----------|
| Inner diameter of the gas nozzle | short       | flush       | long     |
| 13 mm                            | 82-6-2-13-S | 82-6-2-13-F | -        |
| 15 mm                            | 82-6-2-15-S | 82-6-2-15-F | -        |


| Dimensions                  |   |    |      |      |   | Part-No.    |
|-----------------------------|---|----|------|------|---|-------------|
| A                           | B | C  | D    | E    | F |             |
| <b>13 mm inner diameter</b> |   |    |      |      |   |             |
| 45                          | - | 77 | 12.5 | 11.8 | 9 | 82-6-2-13-S |
| 42                          | - | 77 | 12.5 | 11.8 | 9 | 82-6-2-13-F |
| <b>15 mm inner diameter</b> |   |    |      |      |   |             |
| 45                          | - | 77 | 14.5 | 11.8 | 9 | 82-6-2-15-S |
| 42                          | - | 77 | 14.5 | 11.8 | 9 | 82-6-2-15-F |

#### Please note:

Dimensions in mm.



## 12 TCP dimensions



### Overview of standard torch necks air-cooled

| standard dressing | A                | B                  | C            |
|-------------------|------------------|--------------------|--------------|
| Part-No.          | (distance in mm) | (TCP length in mm) | (angle in °) |
| 58-1-00-400-1     | 120              | 461,5              | 0            |
| 58-1-22-350-1     | 75               | 411,5              | 22           |
| 58-1-22-400-1     | 75               | 461,5              | 22           |
| 58-4-330-500-1    | 0                | 500,0              | 30           |
| 58-1-130-450-1    | 120              | 511,5              | 30           |
| 58-1-35-400-1     | 50               | 461,5              | 35           |
| 58-1-45-350-1     | 30               | 411,5              | 45           |
| 58-1-45-400-1     | 30               | 461,5              | 45           |
| 58-1-45-450-1     | 30               | 511,5              | 45           |
| 58-4-345-450-1    | 0                | 450,0              | 45           |
| 58-4-345-567-1    | 0                | 567,0              | 45           |

### Overview ZK type torch necks

| standard dressing | A                | B                  | C            |
|-------------------|------------------|--------------------|--------------|
| Part-No.          | (distance in mm) | (TCP length in mm) | (angle in °) |
| 58-1-245-400-1    | 58               | 461,5              | 45           |

#### Please note:


Dimensions in mm.

## 12 Checking fixtures

### Checking fixtures

To check TCP of torch necks and complete torch.

Checking fixtures are provided for all listed torch necks with Power Clutch torch system. Please contact us for detailed information.



Top view checking fixture



**Please note:**

Further information can be found in our brochure "Checking fixtures" (DOC-0137EN).

## 12 Torch cleaning stations

eReam 2.0 for  
a precise cleaning of  
the torch frontend

For further information  
please scan this QR code:



Pure  
Electric.

**Please note:**

Further information can be found in our eReam 2.0 brochure (DOC-0205EN).

pReam: pneumatic  
cleaning station

Further information can  
be found here:



# Power Clutch water-cooled:

The SKS precision standard  
with water cooling



Further information on the Power Clutch  
water-cooled Weld Package can be found at:



**Please note:**

Further information can be found on our website at  
[www.sks-welding.com/en/products/torch-systems/  
power-clutch-series/power-clutch-water-cooled](http://www.sks-welding.com/en/products/torch-systems/power-clutch-series/power-clutch-water-cooled)

# SKS

WELDING SYSTEMS



**Contact:**  
[sales@  
de.sks-welding.com](mailto:sales@de.sks-welding.com)

**SKS Welding Systems GmbH**

Marie-Curie-Str. 14 | 67661 Kaiserslautern | Germany | Phone +49 6301 7986-0

[www.sks-welding.com](http://www.sks-welding.com)

 /sksweldingsystems

 @sks\_welding\_systems

 /DesignTechnologyPerformance

 /sks-welding-systems